


## NOSE STRIPING DETAILS

## NOSE STRIPING DETAILS




BRIDGE END OR CONC. BARRIER

TYPICAL GUARDRAIL INSTALLATION

TRAFFIC FLOW

A B C

APPROACH END-BRIDGE OR CONCRETE BARRIER



TRAILING END-BRIDGE OR CONCRETE BARRIER

GENERAL NOTES:

- 1-SPECIFICATIONS: GEORGIA STANDARD, CURRENT EDITION, & SUPPLEMENTS THERETO.
- 2-SEE SEPARATE STANDARDS FOR DETAILS OF GUARDRAIL INSTALLATIONS, CONNECTING HARDWARE, AND ANCHORAGES.
- 3-PAYMENT FOR GUARDRAIL AND ANCHORAGES INCLUDES ALL REFLECTORIZED WASHERS AND NOSE STRIPING REQUIRED.
- 4-ADJUSTMENTS OF SPACINGS AND/OR REQUIREMENTS FOR REFLECTIVE WASHERS MAY BE DIRECTED BY THE ENGINEER TO SUIT INDIVIDUAL LOCATIONS.
- 5-WHERE DOUBLE FACED GUARDRAIL IS LOCATED ON THE INSIDE SHOULDER OF MEDIANS, REFLECTORIZED WASHERS SHALL BE REQUIRED ONLY ON THE SIDE WHICH IS NEAREST TO TRAFFIC, UNLESS SPECIFIED OTHERWISE.

2/20/2008 1:08:13 PM \\GDOT-DSN\GOPLLOT\QCF\Road\_Design\Tiff-18x12-to-Tiff-36x24.acf wnaugen C:\Documents and Settings\wnaugen\Desktop\M002418\Construction\Plan Sheet\m002418\_029.tif G0-RD-Plans-Review